



Model Number	Nominal Tonnage <sup>[1]</sup>	Motor HP <sup>[2]</sup>	Airflow (CFM)	Weights (lbs)		H	Connections <sup>[4]</sup>		
				Operating <sup>[3]</sup>	Shipping		Inlet	Outlet	Overflow
VTL-152-M	152	20	45,870	6,580	3,440	5'-2"	8"	8"	3"
VTL-171-L	171	15	39,940	6,820	3,680	6'-7"	8"	8"	3"
VTL-185-M	185	20	43,150	6,960	3,820	6'-7"	8"	8"	3"
VTL-198-N	198	25	46,090	7,000	3,860	6'-7"	8"	8"	3"
VTL-209-0	209	30	48,630	7,040	3,900	6'-7"	8"	8"	3"
VTL-227-0	227	30	46,550	7,470	4,330	8'-2"	8"	8"	3"
VTL-245-P	245	40	58,820	8,970	4,790	6'-7"	8"	8"	3"
VTL-272-P	272	40	56,760	9,490	5,310	8'-2"	8"	8"	3"

**NOTES:**

1. Nominal tons of cooling represents the capability to cool 3 USGPM of water from a 95°F entering water temperature to an 85°F leaving water temperature at a 78°F entering wet-bulb temperature.
2. Fan horsepower is at 0" external static pressure.
3. Operating weight is based on the water level in cold water basin at overflow height.
4. Unless otherwise indicated, all connections 4" and smaller are MPT and connections 6" and larger are beveled for welding.

**Do not use for construction.** Refer to factory certified dimensions. This catalog includes data current at the time of publication, which should be reconfirmed at the time of purchase.