

NC8401 NC8402 NC8403 NC8405

Model note 2	Nominal Tons note 3	Motor hp	dBA 5'-0" from air inlet face	Design Operating Weight lb	Shipping Weight lb	Dimensions			
						L	W	H	A
NC8401G-1	101	2	63	7889	4062	6'-6¼"	12'-10"	10'-2½"	6'-9¾"
NC8401H-1	117	3	65						
NC8401K-1	139	5	71						
NC8401M-1	159	7.5	73						
NC8401N-1	175	10	76						
NC8401P-1	198	15	78						
NC8402G-1	131	2	64	10319	4890	8'-4¾"	14'-2"	10'-3"	8'-8¼"
NC8402H-1	148	3	65						
NC8402K-1	175	5	68						
NC8402M-1	205	7.5	74						
NC8402N-1	228	10	76						
NC8402P-1	256	15	79						
NC8402Q-1	277	20	81	15844	7442	8'-4¾"	18'-2"	11'-11¼"	8'-8¼"
NC8403K-1	213	5	68						
NC8403M-1	243	7.5	72						
NC8403N-1	275	10	76						
NC8403P-1	312	15	79						
NC8403Q-1	342	20	80						
NC8403R-1	366	25	81	19480	8685	9'-10¾"	19'-11"	11'-11¼"	10'-2½"
NC8403S-1	386	30	84						
NC8403T-1	423	40	85						
NC8405N-1	331	10	74						
NC8405P-1	377	15	76						
NC8405Q-1	412	20	78						
NC8405R-1	445	25	81	19480	8685	9'-10¾"	19'-11"	11'-11¼"	10'-2½"
NC8405S-1	472	30	84						
NC8405T-1	515	40	87						

NOTE

- 1 Use this bulletin for preliminary layouts only. Obtain current drawings from your Marley sales representative. All table data is per cell.
- 2 Last numeral of model number indicates number of cells. Change as appropriate for your selection.
- 3 Nominal tons are based upon 95°F HW, 85°F CW, 78°F WB and 3 GPM/ton. The UPDATE web-based selection software provides NC model recommendations based on specific design requirements.
- 4 Standard overflow is a 4" dia. standpipe in the collection basin floor. The standpipe removes for flush-out and draining. See page 18 for side overflow option.
- 5 Outlet sizes vary according to GPM and arrangement. See pages 18 and 19 for outlet sizes and details.
- 6 Makeup water connection may be 1" or 2" dia., depending upon tower heat load, water pressure, and desired connections. See page 13 for additional information.

NC8401 NC8402 NC8403 NC8405

Use this data for preliminary layouts only. Obtain current drawing from your Marley sales representative.

*UPDATE™* web-based selection software, available at [spxcooling.com/update](http://spxcooling.com/update) provides NC model recommendations based on customer's specific design requirements.

*A Sound dBA Approach*

Various low sound options are available from 2 to 19 dB reduction from the standard dBA options in the schematic data table. Consult *UPDATE* selection software for performance, sound levels and dimensions.

